

TABLE OF CONTENTS



01. DOKUWIKI	3
01.01. FORMATTING SYNTAX	3
Basic Text Formatting	3
Links	4
External	4
Internal	4
Interwiki	5
Windows Shares	5
Image Links	6
Footnotes	8
Sectioning	8
HEADLINE LEVEL 1	8
Headline Level 2	8
Headline Level 3	8
Headline Level 4	8
Headline Level 5	8
Media Files	8
Supported Media Formats	15
Fallback Formats	15
Lists	16
Text Conversions	16
Text to Image Conversions	16
Text to HTML Conversions	18
Quoting	18
Tables	19
No Formatting	21
Code Blocks	21
Syntax Highlighting	22
Downloadable Code Blocks	23
RSS/ATOM Feed Aggregation	23
Control Macros	24
Syntax Plugins	25
02. CUSTOMIZATION	28
02.01. SITE IDENTITY	28
Logo	28
Namespace Logo	28

Namespace URL	28
Site Title	29
Site Tagline	29
02.02. NAVIGATION	29
02.03. SIDEBAR	29
02.04. INCLUDED HOOKS	29
02.05. COLOR SCHEMES	30
02.06. CONTENT WIDTH	30
Full Width	30
02.07. TOOLBAR	31
02.08. TOOLTIPS	31
03. PLUGINS	31
03.01. LIST	31
04. DEVELOPMENT	35
04.01. CHANGELOG	35
04.02. PLANNING	35
04.03. FIXES	35

DOCUMENTATION

01. DOKUWIKI

01.01. FORMATTING SYNTAX

 [DokuWiki](#) supports some simple markup language, which tries to make the datafiles to be as readable as possible. This page contains all possible syntax you may use when editing the pages. Simply have a look at the source of this page by pressing “Edit this page”. If you want to try something, just use the [playground](#) page. The simpler markup is easily accessible via  [quickbuttons](#), too.

Basic Text Formatting

DokuWiki supports **bold**, *italic*, underlined and **monospaced** texts. Of course you can combine all these.

```
DokuWiki supports bold, //italic//, __underlined__ and 'monospaced'
texts.
Of course you can __/'combine'/'__ all these.
```

You can use _{subscript} and ^{superscript}, too.

```
You can use <sub>subscript</sub> and <sup>superscript</sup>, too.
```

You can mark something as ~~deleted~~ as well.

```
You can mark something as <del>deleted</del> as well.
```

Paragraphs are created from blank lines. If you want to **force a newline** without a paragraph, you can use two backslashes followed by a whitespace or the end of line.

This is some text with some linebreaks
Note that the two backslashes are only recognized at the end of a line
or followed by
a whitespace \\this happens without it.

```
This is some text with some linebreaks\\ Note that the  
two backslashes are only recognized at the end of a line\\  
or followed by\\ a whitespace \\this happens without it.
```

You should use forced newlines only if really needed.

Links

DokuWiki supports multiple ways of creating links.

External

External links are recognized automagically: <http://www.google.com> or simply www.google.com -
You can set the link text as well: [This Link points to google](#). Email addresses like this one:
andi@splitbrain.org are recognized, too.

```
DokuWiki supports multiple ways of creating links. External links are  
recognized  
automagically: http://www.google.com or simply www.google.com - You can set  
link text as well: [[http://www.google.com|This Link points to google]].  
Email  
addresses like this one: <andi@splitbrain.org> are recognized, too.
```

Internal

Internal links are created by using square brackets. You can either just give a [pagename](#) or use
an additional [link text](#).

```
Internal links are created by using square brackets. You can either just  
give  
a [[pagename]] or use an additional [[pagename|link text]].
```

 [Wiki pagenames](#) are converted to lowercase automatically, special characters are not allowed.

You can use [namespaces](#) by using a colon in the pagename.

```
You can use [[some:namespaces]] by using a colon in the pagename.
```

For details about namespaces see [📖 namespaces](#).

Linking to a specific section is possible, too. Just add the section name behind a hash character as known from HTML. This links to [this Section](#).

```
This links to [[syntax#internal|this Section]].
```

Notes:

- Links to [existing pages](#) are shown in a different style from [nonexisting](#) ones.
- DokuWiki does not use [📖 CamelCase](#) to automatically create links by default, but this behavior can be enabled in the [📖 config](#) file. Hint: If DokuWiki is a link, then it's enabled.
- When a section's heading is changed, its bookmark changes, too. So don't rely on section linking too much.

Interwiki

DokuWiki supports [📖 Interwiki](#) links. These are quick links to other Wikis. For example this is a link to Wikipedia's page about Wikis: [📖 Wiki](#).

```
DokuWiki supports [[doku>Interwiki]] links. These are quick links to other Wikis.  
For example this is a link to Wikipedia's page about Wikis: [[wp>Wiki]].
```

Windows Shares

Windows shares like [this](#) are recognized, too. Please note that these only make sense in a homogeneous user group like a corporate [📖 Intranet](#).

```
Windows Shares like [[\\server\share|this]] are recognized, too.
```

Notes:

- For security reasons direct browsing of windows shares only works in Microsoft Internet Explorer per default (and only in the “local zone”).

- For Mozilla and Firefox it can be enabled through different workaround mentioned in the [Mozilla Knowledge Base](#). However, there will still be a JavaScript warning about trying to open a Windows Share. To remove this warning (for all users), put the following line in `conf/lang/en/lang.php` (more details at [🗨 localization](#)):


`conf/lang/en/lang.php`

```
<?php
/**
 * Customization of the english language file
 * Copy only the strings that needs to be modified
 */
$lang['js']['nosmblinks'] = '';
```

Image Links

You can also use an image to link to another internal or external page by combining the syntax for links and [images](#) (see below) like this:

```
[[http://php.net|{{wiki:logo-disqus.png}}]]
```



Please note: The image formatting is the only formatting syntax accepted in link names.

The whole [image](#) and [link](#) syntax is supported (including image resizing, internal and external images and URLs and interwiki links).

Footnotes

You can add footnotes ¹⁾ by using double parentheses.

You can add footnotes ((This is a footnote)) by using double parentheses.

Sectioning

You can use up to five different levels of headlines to structure your content. If you have more than three headlines, a table of contents is generated automatically - this can be disabled by including the string `~~NOTOC~~` in the document.

HEADLINE LEVEL 1

Headline Level 2

Headline Level 3


Headline Level 4

Headline Level 5

```
===== Headline Level 1 =====  
=====  
==== Headline Level 2 =====  
=====  
==== Headline Level 3 =====  
=====  
==== Headline Level 4 =====  
=====  
==== Headline Level 5 =====  
=====
```


By using four or more dashes, you can make a horizontal line:


Media Files

You can include external and internal  images, videos and audio files with curly brackets. Optionally you can specify the size of them.

Real size:



Resize to given width: 

Resize to given width and height²⁾: 

Resized external image:




```
Real size:                {{wiki:logo-disqus.png}}  
Resize to given width:   {{wiki:logo-disqus.png?50}}  
Resize to given width and height: {{wiki:logo-disqus.png?200x50}}  
Resized external image:  
{{https://www.php.net/images/php.gif?200x50}}
```

By using left or right whitespaces you can choose the alignment.







```
{{ wiki:logo-disqus.png }}  
{{wiki:logo-disqus.png }}  
{{ wiki:logo-disqus.png }}
```

Of course, you can add a title (displayed as a tooltip by most browsers), too.



`{{ wiki:logo-disqus.png |This is the caption}}`

For linking an image to another page see [Image Links](#) above.

Supported Media Formats

DokuWiki can embed the following media formats directly.

Image	<code>gif, jpg, png</code>
Video	<code>webm, ogv, mp4</code>
Audio	<code>ogg, mp3, wav</code>
Flash	<code>swf</code>

If you specify a filename that is not a supported media format, then it will be displayed as a link instead.

By adding `?linkonly` you provide a link to the media without displaying it inline

```
{{wiki:logo-disqus.png?linkonly}}
```

[logo-disqus.png](#) This is just a link to the image.

Fallback Formats

Unfortunately not all browsers understand all video and audio formats. To mitigate the problem, you can upload your file in different formats for maximum browser compatibility.

For example consider this embedded mp4 video:

```
{{video.mp4|A funny video}}
```

When you upload a `video.webm` and `video.ogv` next to the referenced `video.mp4`, DokuWiki will automatically add them as alternatives so that one of the three files is understood by your browser.

Additionally DokuWiki supports a “poster” image which will be shown before the video has started. That image needs to have the same filename as the video and be either a jpg or png file. In the example above a `video.jpg` file would work.

Lists

Dokuwiki supports ordered and unordered lists. To create a list item, indent your text by two spaces and use a `*` for unordered lists or a `-` for ordered ones.

- This is a list
 - The second item
 - You may have different levels
 - Another item
1. The same list but ordered
 2. Another item
 1. Just use indentation for deeper levels
 3. That's it

```
* This is a list
* The second item
  * You may have different levels
* Another item

- The same list but ordered
- Another item
  - Just use indentation for deeper levels
- That's it
```

Also take a look at the [FAQ on list items](#).

Text Conversions






















DokuWiki can convert certain pre-defined characters or strings into images or other text or HTML.

The text to image conversion is mainly done for smileys. And the text to HTML conversion is used for typography replacements, but can be configured to use other HTML as well.

Text to Image Conversions

DokuWiki converts commonly used [emoticons](#) to their graphical equivalents. Those [Smileys](#) and other images can be configured and extended. Here is an overview of Smileys included in

DokuWiki:

-  8-)
-  8-O
-  :-(
-  :-)
-  =)
-  :-/
-  :-\
-  :-?
-  :-D
-  :-P
-  :-O
-  :-X
-  :-|
-  ;-)
-  ^_^
-  m(
-  :?:
-  !:!
-  LOL
-  **Fix Me!** FIXME
-  **Delete!** DELETEME

Text to HTML Conversions

Typography: [DokuWiki](#) can convert simple text characters to their typographically correct entities. Here is an example of recognized characters.

```
→ ← ↔ ⇒ ⇐ ⇔ » « - — 640×480 © ™ ® “He thought 'It's a man's world'...”
```

```
-> <- <-> => <= <=> >> << -- --- 640x480 (c) (tm) (r)  
"He thought 'It's a man's world'..."
```

The same can be done to produce any kind of HTML, it just needs to be added to the [pattern file](#).

There are three exceptions which do not come from that pattern file: multiplication entity (640×480), 'single' and “double quotes”. They can be turned off through a [config option](#).

Quoting

Some times you want to mark some text to show it's a reply or comment. You can use the following syntax:

```
I think we should do it  
> No we shouldn't  
>> Well, I say we should  
> Really?  
>> Yes!  
>>> Then lets do it!
```

I think we should do it

```
No we shouldn't  
| Well, I say we should  
| Really?
```

| Yes!

| Then lets do it!

Tables

DokuWiki supports a simple syntax to create tables.

Heading 1	Heading 2	Heading 3
Row 1 Col 1	Row 1 Col 2	Row 1 Col 3
Row 2 Col 1	some colspan (note the double pipe)	
Row 3 Col 1	Row 3 Col 2	Row 3 Col 3

Table rows have to start and end with a | for normal rows or a ^ for headers.

```

^ Heading 1      ^ Heading 2      ^ Heading 3      ^
| Row 1 Col 1   | Row 1 Col 2   | Row 1 Col 3   |
| Row 2 Col 1   | some colspan (note the double pipe) ||
| Row 3 Col 1   | Row 3 Col 2   | Row 3 Col 3   |

```

To connect cells horizontally, just make the next cell completely empty as shown above. Be sure to have always the same amount of cell separators!

Vertical tableheaders are possible, too.

	Heading 1	Heading 2
Heading 3	Row 1 Col 2	Row 1 Col 3
Heading 4	no colspan this time	
Heading 5	Row 2 Col 2	Row 2 Col 3

As you can see, it's the cell separator before a cell which decides about the formatting:

```

|           ^ Heading 1           ^ Heading 2           ^
^ Heading 3 | Row 1 Col 2           | Row 1 Col 3           |
^ Heading 4 | no colspan this time |           |
^ Heading 5 | Row 2 Col 2           | Row 2 Col 3           |

```

You can have rowspans (vertically connected cells) by adding `:::` into the cells below the one to which they should connect.

Heading 1	Heading 2	Heading 3
Row 1 Col 1	this cell spans vertically	Row 1 Col 3
Row 2 Col 1		Row 2 Col 3
Row 3 Col 1		Row 2 Col 3

Apart from the rowspan syntax those cells should not contain anything else.

```

^ Heading 1   ^ Heading 2           ^ Heading 3           ^
| Row 1 Col 1 | this cell spans vertically | Row 1 Col 3           |
| Row 2 Col 1 | :::                   | Row 2 Col 3           |
| Row 3 Col 1 | :::                   | Row 2 Col 3           |

```

You can align the table contents, too. Just add at least two whitespaces at the opposite end of your text: Add two spaces on the left to align right, two spaces on the right to align left and two spaces at least at both ends for centered text.

Table with alignment		
right	center	left
left	right	center
XXXXXXXXXXXXX	XXXXXXXXXXXXX	XXXXXXXXXXXXX

This is how it looks in the source:

```

^           Table with alignment           ^^^
|           right|      center      |left      |
|left      |           right|      center      |
|xxxxxxxxxxxx|xxxxxxxxxxxx|xxxxxxxxxxxx|

```

Note: Vertical alignment is not supported.

No Formatting

If you need to display text exactly like it is typed (without any formatting), enclose the area either with `<nowiki>` tags or even simpler, with double percent signs `%%`.

This is some text which contains addresses like this: `http://www.splitbrain.org` and `**formatting**`, but nothing is done with it. The same is true for `//__this__ text//` with a smiley `;-)`.

```

<nowiki>
This is some text which contains addresses like this:
http://www.splitbrain.org and **formatting**, but nothing is done with it.
</nowiki>
The same is true for %%//__this__ text// with a smiley ;-)%%.

```

Code Blocks

You can include code blocks into your documents by either indenting them by at least two spaces (like used for the previous examples) or by using the tags `<code>` or `<file>`.

```

This is text is indented by two spaces.

```

```

This is preformatted code all spaces are preserved: like          <-this

```

```

This is pretty much the same, but you could use it to show that you quoted a
file.

```

Those blocks were created by this source:

```

This is text is indented by two spaces.

```

```

<code>

```

This is preformatted code all spaces are preserved: like `<-this`
</code>

`<file>`
This is pretty much the same, but you could use it to show that you quoted a file.
`</file>`

Syntax Highlighting

[DokuWiki](#) can highlight sourcecode, which makes it easier to read. It uses the [GeSHi](#) Generic Syntax Highlighter - so any language supported by GeSHi is supported. The syntax uses the same code and file blocks described in the previous section, but this time the name of the language syntax to be highlighted is included inside the tag, e.g. `<code java>` or `<file java>`.

```
/**
 * The HelloWorldApp class implements an application that
 * simply displays "Hello World!" to the standard output.
 */
class HelloWorldApp {
    public static void main(String[] args) {
        System.out.println("Hello World!"); //Display the string.
    }
}
```

The following language strings are currently recognized: *4cs 6502acme 6502kickass 6502tasm 68000devpac abap actionscript3 actionscript ada aimms algol68 apache applescript apt_sources arm asm asp asymptote autoconf autohotkey autoit avisynth awk bascomavr bash basic4gl batch bf biblatex bibtex blitzbasic bnf boo caddcl cadlisp ceylon cfdg cfm chaiscript chapel cil c_loadrunner clojure c_mac cmake cobol coffeescript c cpp cpp-qt cpp-winapi csharp css cuesheet c_winapi dart dcl dcpu16 dcs delphi diff div dos dot d ecmascript eiffel email epc e erlang euphoria ezt f1 falcon fo fortran freebasic freeswitch fsharp gambas gdb genero genie gettext glsl gml gnuplot go groovy gwbasic haskell haxe hicest hq9plus html html4strict html5 icon idl ini inno intercal io ispfpanel java5 java javascript jcl j jquery julia kixtart klonec klonecpp kotlin latex lb ldif lisp llvm locobasic logtalk lolcode lotusformulas lotusscript lscript lsl2 lua m68k magiksf make mapbasic mathematica matlab mercury metapost mirc mk-61 mmix modula2 modula3 mpasm mxml mysql nagios netrexx newlisp nginx nimrod nsis oberon2 objc object ocaml-brief ocaml octave oobas oorexx oracle11 oracle8 oxygene oz parasail parigp pascal pcre perl6 perl per pf phix php-brief php pic16 pike pixelbender pli plsql postgresql postscript povray*

powerbuilder powershell proftpd progress prolog properties providex purebasic pycon pys60 python qbasic qml q racket rails rbs rebol reg rexx robots roff rpmspec rsplus ruby rust sas sass scala scheme scilab scl sdlbasic smalltalk smarty spark sparql sql sshconfig standardml stonemscript swift systemverilog tclegg tcl teraterm texgraph text thinbasic tsql twig typoscript unicon upc urbi uscript vala vbnet vb vbscript vedit verilog vhdl vim visualfoxpro visualprolog whitespace whois winbatch wolfram xbasic xml xojo xorg_conf xpp yaml z80 zxbasic

There are additional [advanced options](#) available for syntax highlighting, such as highlighting lines or adding line numbers.

Downloadable Code Blocks

When you use the `<code>` or `<file>` syntax as above, you might want to make the shown code available for download as well. You can do this by specifying a file name after language code like this:

```
<file php myexample.php>
<?php echo "hello world!"; ?>
</file>
```

myexample.php

```
<?php echo "hello world!"; ?>
```

If you don't want any highlighting but want a downloadable file, specify a dash (-) as the language code: `<code - myfile.foo>`.

RSS/ATOM Feed Aggregation

[DokuWiki](#) can integrate data from external XML feeds. For parsing the XML feeds, [SimplePie](#) is used. All formats understood by SimplePie can be used in DokuWiki as well. You can influence the rendering by multiple additional space separated parameters:

Parameter	Description
any number	will be used as maximum number items to show, defaults to 8

Parameter	Description
reverse	display the last items in the feed first
author	show item authors names
date	show item dates
description	show the item description. All HTML tags will be stripped
nosort	do not sort the items in the feed
n[dhm]	refresh period, where d=days, h=hours, m=minutes. (e.g. 12h = 12 hours).

The refresh period defaults to 4 hours. Any value below 10 minutes will be treated as 10 minutes. [DokuWiki](#) will generally try to supply a cached version of a page, obviously this is inappropriate when the page contains dynamic external content. The parameter tells [DokuWiki](#) to re-render the page if it is more than *refresh period* since the page was last rendered.

By default the feed will be sorted by date, newest items first. You can sort it by oldest first using the **reverse** parameter, or display the feed as is with **nosort**.

Example:

```
{{rss>http://slashdot.org/index.rss 5 author date 1h }}
```

- [SpaceX's Upgraded Starship V3 Launches For First Time](#) by BeauHD (2026/05/22 20:30)
- [Google API Keys Remain Active After Deletion](#) by BeauHD (2026/05/22 19:00)
- [Major Streamers Must Pay 15% of Revenues To Canadian Content, CRTC Says](#) by BeauHD (2026/05/22 18:00)
- [NTSB Wants PDF Removed After It Exposed Final Cockpit Audio From UPS Crash](#) by BeauHD (2026/05/22 17:00)
- [Trump Mobile Exposed Customers' Personal Data, Including Phone Numbers and Home Addresses](#) by BeauHD (2026/05/22 16:00)

Control Macros

Some syntax influences how DokuWiki renders a page without creating any output it self. The

following control macros are available:

Macro	Description
~~NOTOC~~	If this macro is found on the page, no table of contents will be created
~~NOCACHE~~	DokuWiki caches all output by default. Sometimes this might not be wanted (eg. when the <php> syntax above is used), adding this macro will force DokuWiki to rerender a page on every call

Syntax Plugins

DokuWiki's syntax can be extended by [Plugins](#). How the installed plugins are used is described on their appropriate description pages. The following syntax plugins are available in this particular DokuWiki installation:

- [acknowledge plugin 2026-04-02](#) by [Andreas Gohr, Anna Dabrowska](#)
Let users acknowledge pages
- [Add New Page plugin 2026-04-24](#) by [Damien Regad, Benjamin Santalucia, Sam Wilson and other contributors](#)
Adds a "new page form" to any wiki page.
- [Barcodes 2024-09-17](#) by [Matthias Lohr](#)
Barcodes (1D & 2D) for DokuWiki
- [Blockquote Plugin 2020-09-27](#) by [Anika Henke \(previous author: Gina Haeussge\)](#)
Write quotations in a semantically correct way
- [Blog 2023-10-24](#) by [Michael Hamann, Michael Klier, Gina Haeussge](#)
Use DokuWiki as blogging tool. (previous authors: Esther Brunner)
- [Bureaucracy Plugin 2025-03-06](#) by [Andreas Gohr](#)
Create forms and generate pages or emails from them
- [Cloud Plugin 2023-02-11](#) by [Michael Hamann, Michael Klier, Gina Haeussge](#)
Displays the most used words in a word cloud.
- [CSV Plugin 2025-06-04](#) by [Andreas Gohr](#)
Displays a CSV file, or inline CSV data, as a table
- [Structured Data Plugin 2024-01-30](#) by [Andreas Gohr](#)
Add and query structured data in your wiki
- [Diagrams plugin 2025-10-15](#) by [Innovakom + CosmoCode](#)
Embed diagrams.net editor (formerly draw.io)
- [discussion plugin 2025-07-04](#) by [Michael Hamann, Gerrit Uitslag, Gina Häussge, Christopher Smith, Michael Klier, Esther Brunner, Matthias Schulte](#)

- Provides discussion functionality for wiki pages
- [Disqus Plugin 2016-08-09](#) by [Andreas Gohr](#)
Embed Disqus discussion threads
 - [Dw2Pdf plugin 2026-01-08](#) by [Andreas Gohr](#) and [Luigi Micco](#)
DokuWiki to PDF converter
 - [Editor Plugin 2020-12-13](#) by [Gina Häußge](#), [Michael Klier](#), [Esther Brunner](#)
Displays a list of recently changed wiki pages by a given author
 - [Feed Plugin 2020-10-26](#) by [Michael Klier](#), [Gina Haeussge](#)
Generates feeds for other plugins
 - [folded plugin 2023-07-22](#) by [Michael Hamann](#), [Fabian van-de-I_Isle](#), [Christopher Smith](#), [Esther Brunner](#)
Foldable page sections
 - [Gallery Plugin 2024-04-30](#) by [Andreas Gohr](#)
Creates a gallery of images from a namespace or RSS/ATOM feed
 - [gh plugin 2025-06-04](#) by [Andreas Gohr](#)
andi@splitbrain.org
 - [hidepages plugin 2013-08-02](#) by [Matthias Schulte](#)
Hide pages from search results and/or sitemap
 - [Icons Plugin 2024-10-30](#) by [Giuseppe Di Terlizzi](#)
Embed icons in Dokuwiki
 - [include plugin 2025-07-22](#) by [Michael Hamann](#), [Gina Häussge](#), [Christopher Smith](#), [Michael Klier](#), [Esther Brunner](#)
Functions to include another page in a wiki page
 - [Indexmenu Plugin 2024-01-05](#) by [Samuele Tognini](#), [Gerrit Uitslag](#)
Show a customizable and sortable index for a namespace
 - [Info Plugin 2020-06-04](#) by [Andreas Gohr](#)
Displays information about various DokuWiki internals
 - [keyboard 2023-02-23](#) by [Gina Häußge](#)
The keyboard plugin provides a combined syntax and action plugin in order to markup text as keyboard keys, similar to (and making use of) the existing (X)HTML tag `<kbd>...</kbd>`. A quick button for the markup is automatically inserted into the toolbar of the edit form.
 - [Linkback plugin 2023-12-30](#) by [Michael Hamann](#), [Gina Häußge](#)
Adds Trackback and Pingback support to DokuWiki
 - [log plugin 2019-02-27](#) by [Adrian Lang](#)
Provide simple logs
 - [mermaid Plugin 2026-05-15](#) by [Robert Weinmeister](#)
JavaScript based diagramming and charting tool that renders Markdown-inspired text definitions to create and modify diagrams dynamically.
 - [nspages plugin 2024-10-07](#) by [Guillaume Turri](#)

Presents a toc of the selected namespace using `<nspages>`

- [Pageimage 2018-10-12](#) by [lisps](#), [peterfromearth](#)
Functions to return image for given page
- [Pagelist Plugin 2023-08-27](#) by [Matthias Schulte](#), [Michael Hamann](#), [Michael Klier](#), [Gina Häussge](#)
Lists pages in a nice formatted way
- [PDF.js 2020-06-29](#) by [Szymon Olewniczak](#)
Show pdf files using PDF.js
- [Publish Plugin 2025-07-14](#) by [Jarrod Lowe](#), [Andreas Gohr](#), [Dominik Eckelmann](#)
Integrate a publishing process into DokuWiki
- [Quality Control Plugin 2025-11-10](#) by [Andreas Gohr](#)
Check the page structure for quality problems
- [Search Form Plugin 2024-02-08](#) by [Gerrit Uitslag](#), (previous: [Adolfo González Blázquez](#))
Inserts a search form in any page
- [simplenavi plugin 2026-02-02](#) by [Andreas Gohr](#)
Create a simple navigation tree based on namespaces
- [Socialite plugin 2019-01-01](#) by [Fernando Ribeiro](#)
Lightweight responsive social buttons
- [starred plugin 2023-06-13](#) by [Andreas Gohr](#)
Personal bookmarking for pages
- [svgEmbed plugin 2025-07-07](#) by [Emma Bowers](#)
Allows the use of the standard media syntax, but SVG files are placed with the `<object>` or `<embed>` tag, not the `` tag.
- [Tag Button plugin 2024-10-18](#) by [Louis Ouellet](#)
Add a tag via a button
- [tagsections plugin 2026-01-21](#) by [i-net software / Gerry Weißbach](#)
Add tags to sections using the taggadd gui
- [Tag Plugin 2023-10-17](#) by [Michael Hamann](#), [Gina Häussge](#), [Christopher Smith](#), [Michael Klier](#), [Esther Brunner](#)
tag wiki pages
- [Task Plugin 2020-09-26](#) by [Michael Klier](#), [Gina Häussge](#)
Brings task management to DokuWiki.
- [ToDo 2025-08-26](#) by [Leo Eibler](#), [Christian Marg](#), [Markus Gschwendt](#), [Robert Weinmeister](#)
Create a checkbox based todo list with optional user assignment (basic syntax: `<todo>This is a ToDo</todo>`). It can also be used as a lightweight task list management system.
- [Translation Plugin 2025-05-20](#) by [Andreas Gohr](#)
Supports the easy setup of a multi-language wiki.
- [Typography plugin 2020-07-31](#) by [Satoshi Sahara](#)
Enable typesetting capabilities with CSS font properties such as font face, size, weight, and

color of text

- [Variable Plugin](#) 2020-09-27 by [Gina Häußge](#), [Michael Klier](#), [Esther Brunner](#), [Luis Machuca Bezzaza](#), [Marek Ištváněk](#)
Insert dynamic variables.
- [Video Sharing Site Plugin](#) 2025-12-10 by [Andreas Gohr](#)
Easily embed videos from various Video Sharing sites. Example: `{{youtube>XXXXXX}}`
- [Wrap Plugin](#) 2023-08-13 by [Anika Henke](#)
Universal plugin which combines functionalities of many other plugins. Wrap wiki text inside containers (divs or spans) and give them a class (choose from a variety of preset classes), a width and/or a language with its associated text direction.
- [yourip plugin](#) 2022-08-07 by [Artem Sidorenko](#), [Hella Breitkopf](#)
Show the ip information of visitor

02. CUSTOMIZATION

02.01. SITE IDENTITY

Logo

You can change the logo, favicon and apple touch icon the [same way as for the dokuwiki template](#).

Namespace Logo

If you enable `doLogoChangesByNamespace` in the template's configuration, Writr will use the closest logo as the site logo. Namespace Logos can be added using the media library. To show a different logo in a namespace, just make sure to add the custom `logo.png` in the namespace. This feature is recursive.

Namespace URL

If you enable `doLogoLinkChangesByNamespace` in the template's configuration, Writr will set the logo's url to the same namespace it found the logo.

Site Title

If you enable `doTitleChangesByNamespace` in the template's configuration, Writr will set the title found in the closest `nstitle.txt` page.

Site Tagline

If you enable `doTaglineChangesByNamespace` in the template's configuration, Writr will set the title found in the closest `nstagline.txt` page.

02.02. NAVIGATION

This templates supports multiple levels of a navigation. For that to work you need to add a page called `topnav` and add a list of links to it. (No other content is supported.) The example in the screenshot uses this as the content for the `topnav` page:

topnav.txt

```
~~NOCACHE~~
* [[:start|Home]]
* [[wiki:DokuWiki]]
  * [[wiki:Syntax]]
* [[:Sample Page]]
```

02.03. SIDEBAR

The content of a standard sidebar as configured in [Configuration Setting: sidebar](#) will be added between the navigation and the tools list.

02.04. INCLUDED HOOKS

Include hooks allow you to add additional HTML or PHP to the template without modifying any of

the template files themselves. This template supports the [same include hooks as the dokuwiki template](#).

02.05. COLOR SCHEMES

The original WordPress theme came with 6 different colour schemes. Those can easily be achieved by changing the `theme_color` and `theme_color_alt` values in your local `style.ini` to the following:

Color Scheme	theme_color	theme_color_alt
Turquoise	<code>#1abc9c</code>	<code>#16a085</code>
Red	<code>#e74c3c</code>	<code>#c0392b</code>
Purple	<code>#a162ba</code>	<code>#8e44ad</code>
Grey	<code>#95a5a6</code>	<code>#7f8c8d</code>
Green	<code>#2ecc71</code>	<code>#27ae60</code>
Blue	<code>#3498db</code>	<code>#2980b9</code>

This should actually be done in the [styling plugin](#) over the admin interface. No need to go out of your way to edit `style.ini`.

02.06. CONTENT WIDTH

The width of the content area can be adjusted with the `content_width` variable in the `style.ini`. Since DokuWiki version 2015-08-10 "Detritus" you can do that more easily with the [styling plugin](#) over the admin interface. This is limited to px size.

Full Width

If you enable `makeFullWidth` in the template's configuration, Writr will use `content_border` as the right border of the content.

02.07. TOOLBAR

If you enable `useToolBar` in the template's configuration, Writr will use a page called `topbar` to setup the toolbar. This toolbar support the same formatting as the Navigation `topnav` page.

topbar.txt

```
~~NOCACHE~~  
* [[info@domain.com]]
```

02.08. TOOLTIPS

If you enable `useToolTips` in the template's configuration, Writr will use create stylish tooltips to replace the default browser tooltips.

03. PLUGINS

03.01. LIST

Plugin	Documentation	Tested	Themed
ACL Manager	acl		
Add New Page	addnewpage		
Advanced DokuWiki	advanced		
Plain Auth	authplain		

Plugin	Documentation	Tested	Themed
Avatar	avatar		
Blockquote	blockquote		
Blog	blog		
Bloglinks	Bloglinks		
Bureaucracy	bureaucracy		
Captcha	captcha		
Cloud	cloud		
Comment Syntax Support	commentsyntax		
Configuration Manager	config		
Copy 2 Clipboard	copy2clipboard		
Cookie Banner	cookiebanner		
Structured Data	data		
Deny Actions	denyactions		
Diagrams	diagrams		
Discussion	discussion		
Disqus	disqus		
DW2pdf	dw2pdf		
Extension Manager	extension		
Folded	folded		
Font-Awesome	fontawesome		

Plugin	Documentation	Tested	Themed
Gallery	gallery		
GH	gh		
Heatmap	heatmap		
Hidepages	hidepages		
Icons	icons		
ImgPaste	imgpaste		
Include	Include		
Info	info		
Index Menu	Index Menu		
Keyboard	keyboard		
Linkback	linkback		
Log Viewer	logviewer		
Move	move		
NS Pages	nspages		
Page Buttons	pagebuttons		
Pagelist	pagelist		
Prosemirror	prosemirror		
Publish	publish		
Revert Manager	revert		
SafeFNRecode	safefnrecode		

Plugin	Documentation	Tested	Themed
Search Form	searchform		
Socialite	socialite		
SQLITE	sqlite		
Starred	starred		
Struct	Struct		
Styling	styling		
SVG Embed	svgembed		
Tag	tag		
Tag Alerts	tagalerts		
Tag Button	tagbutton		
Tag Sections	tagsections		
Task	task		
Task Extra	taskextra		
Translation	translation		
Typography	typography		
Upgrade	upgrade		
User History Manager	userhistory		
User Manager	usermanager		
User Page	userpage		
Video Sharing Site	vshare		

Plugin	Documentation	Tested	Themed
Wrap	Wrap		
Your IP	yourip		

04. DEVELOPMENT

04.01. CHANGELOG

- [Merge pull request #34 from LaswitchTech/dev](#) (2026/05/11 12:02)
- [Version Upped](#) (2026/05/11 12:01)
- [General: Version bumped to v2026-05-12](#) (2026/05/11 11:57)
- [Merge pull request #31 from LaswitchTech/dev](#) (2026/05/11 11:56)
- [General: Version bumped to v2026-05-11](#) (2026/05/11 11:55)
- [BUGFIX: Updated the default color of the picture borders](#) (2026/03/30 11:45)
- [General: Added icons for pixelfed.social, bandcamp.com, last.fm and l...](#) (2026/03/30 11:44)
- [General: Adding the ttf files.](#) (2026/03/26 08:28)

04.02. PLANNING

- Add more fonts (suggestions?)
- Add variables support for the template (note: May move this to a plugin instead)
- Add toggle-able sidebar
- Investigate an issue with the Struct Plugin

04.03. FIXES

Fixes Proposed to Plugin Creators to Complete Compatibility.

Plugin	Issue	Repository	Pull Request	Status
Bloglinks	Issue	GitHub Repository	Pull Request	Merged
Linkback	Issue	GitHub Repository	Pull Request	Merged
Task	—	GitHub Repository	Pull Request	Open
Bureaucracy	Issue	GitHub Repository	Pull Request	Open
Tag Sections	Issue	GitHub Repository	Pull Request	Open

1)

This is a footnote

2)

when the aspect ratio of the given width and height doesn't match that of the image, it will be cropped to the new ratio before resizing

From:

<https://laswitchtech.com/> - **LaswitchTech**

Permanent link:

<https://laswitchtech.com/en/projects/writr/documentation/index>

Last update: **2024/11/06 14:35**

